

GLAKS features top aesthetic properties, especially in the gloss surface finish. Because it is hygroscopic, the surface absorbs air humidity for 48-72 hours, only then reaching full hardness and durability. Remove the protective foil only after complete assembly and installation, in a dry and dust-free environment, and make sure that the product surface is not scratched by nails or sharp or abrasive items.

TYPE OF STAINS	RECOMMENDED CLEANING AGENTS AND TECHNIQUES
Syrup, fruit juice, jam, spirits, milk, tea, coffee, wine, soap, ink	A wet sponge
Animal and vegetable fats, sauces, dried blood, dried wine and spirits, eggs, black smoke, vegetable gelatine, vinyl adhesives, organic residues, watercolours, adhesive residues after removing the protective foil, gum arabic, acrylic, or vegetable gum	A sponge soaked in cold water with soap or a household cleaner – rinse well and dry with a piece of cotton cloth
Hairspray, vegetable or castor oil, ballpoint pens and markers, wax, greasy make-up or powder, stains after the evaporation of solvents	Alcohol and acetone applied with a piece of cotton cloth – rinse well and dry with a piece of cotton cloth or paper kitchen towels
Silicone residues	Very gently scrape with a wooden or plastic tool so as not to scratch the surface; after complete drying, they can no longer be removed
Limescale	Detergents containing a low concentration of citric and acetic acid (maximum 10%).

#### Cleaning Recommendation

**Warning:** Avoid increased mechanical stress, especially scratching and wiping the surface with items with a sharp or abrasive surface – do not use cleaning sponges with a rough side, brushes, scrapers, steel wool, etc.).